

Key Benefits

- Recommended for long-term storage
- Excellent ferrous and non-ferrous corrosion protection properties
- Superior vapor phase corrosion protection
- Resistant to microbial infection
- Fully compatible with Oceanic HW Subsea Production Control fluids, Erifon BOP and Erifon motion compensator fluids
- No colour taint of subsequent installed control fluid
- Manufactured to NAS 1638/AS 4059 Class 6/6b-f or better cleanliness
- Meets stringent global environmental acceptability requirements
- Free Fluid Monitoring programme can optimise flushing & testing operations

Description

Oceanic EPF fluids are high-quality water-based fluids. These ready to use fluids protect the internals of hydraulic systems during long-term storage.

Oceanic EPF fluids are compatible with each other, with Oceanic HW production control fluids, Erifon BOP and Erifon motion compensator fluids. Fluids differ in glycol content and geographic availability.



Typical Physical Properties

	Oceanic EPF US	Oceanic EPF 2 UK
Appearance	Clear Colorless Liquid	Clear Colorless Liquid
pH	9.9	9.3
Specific Gravity @15.6°C	1.08	1.05
Kinematic Viscosity (cSt)		
-20°C (-4°F)	40	24
0°C (32°F)	15.6	7
40°C (104°F)	3.5	4
Pour Point	-50°C (-58°F)	-25°C (-12°F)

For further recommendations, technical information, Health & Safety data sheets, OEM or environmental approvals, email wigansales@macdermid.com

THE CONTROL FLUID TECHNOLOGY LEADER

Oceanic EPF Fluids | Issue No. 12 Date: Oct 2015 | www.macdermid.com/offshore

OCEANIC EPF

Environmental Information

MacDermid maintains worldwide environmental approvals and can offer Oceanic Storage fluids suitable for use in every exploration and production region around the world. The current environmental status of Oceanic EPF fluids in your area can be obtained from our environmental specialists.

Storage

Oceanic EPF fluids should be stored in dry conditions, ideally out of direct sunlight. Normal storage temperature range is 5 to 40°C.

Material Compatibility

Oceanic EPF fluids contain performance additives which ensure high levels of compatibility with materials typically used in subsea production control equipment during long storage periods. Extensive material compatibility tests have been performed with Oceanic EPF fluids.

Ferrous metals (cast iron, carbon steel, low & high alloy steels, stainless steels...)	Compatible
Non-ferrous metals (copper, brass, bronze and other metals and alloys*)	Compatible with alloys typically used in subsea production control equipment. Avoid Zn, Cd, Pb and Mg metals. Aluminum should be hard anodized.
Coatings and ceramic materials	Avoid porous coatings. Compatible with most ceramic parts. Check ceramic coatings
Packaging & sealing materials (elastomers and thermoplastics*)	Compatible with standard NBR, HNBR, FFKM, VMQ/FMVQ, CR, TFE/PTFE, PEEK. Some FKM & AU/EU/PU have proven to be incompatible
Umbilical hose liner thermoplastics	Compatible with Nylon 11, PE and Polyether ester copolymers
Absorbent gasket materials	Avoid cork, leather, cotton impregnated materials
Paints	Avoid painting internal surfaces Cured epoxy, phenolic and nylon based paints are satisfactory. Avoid less resistant paints as they soften. Wash spillages immediately with water
Filter elements	Polypropylene and glass fiber filter elements recommended over paper filters

* As material compatibility varies from compound to compound and supplier to supplier, consult supplier for recommendations or request specific compatibility tests.

MacDermid Offshore Solutions A Subsidiary of MacDermid Group

Manufacturing Locations

United Kingdom

MacDermid Offshore Solutions UK
Cale Lane, New Springs
Wigan
WN2 1JR
Tel: +44 (0)1942 501000
Fax: +44 (0)1942 501110
E-mail: wigansales@macdermid.com

Brazil (Cambé)

MacDermid Offshore do Brasil
Rua Afonso Figueiró, 43
Parque Industrial José Garcia
Gimenes, Cambé, Paraná CEP: 86183-752
Tel: +55 43 3223 3355
E-mail: offshoresales@macdermidfluidos.com.br

USA

MacDermid Offshore Solutions Ltd
223 N Brockman
Pasadena, TX 77506
USA Tel: (US) 800 521 2589
Outside US: +1 713 472 5081
Fax: 713 472 2440
E-mail: offshoreorders@macdermid.com

Brazil

MacDermid Anion
Rua Eli Walter Cesar, 110
Jd Alvorada
Jandira, São Paulo Cep.: 06612-130
Tel: +55 11 4789 8585
E-mail: offshoresales@macdermidfluidos.com.br

Australia

MacDermid Offshore Solutions
29 Dennis Street
Campbellfield, Melbourne
Victoria 3061
Tel: +61 3 9303 5150
Fax: +61 3 9303 5166
E-mail: wigansales@macdermid.com

For further recommendations, technical information, Health & Safety data sheets, OEM or environmental approvals, email wigansales@macdermid.com

THE CONTROL FLUID TECHNOLOGY LEADER

Oceanic EPF Fluids | Issue No. 12 Date: Oct 2015 | www.macdermid.com/offshore